REDFIT 3.5

Estimating red-noise spectra directly from unevenly spaced paleoclimatic time series

Manual (March 2001)

This program has been placed in the public domain. You should feel free to pass the program to your colleagues as long as you do not charge for it and you include each of the original files in unaltered form.

The program has been tested, though not rigorously, and is correct to the best of our knowledge. If you find any errors or have any suggestions, we would appreciate it if you would let us know:

Michael Schulz

Institute for Geosciences, Univ. Kiel, Olshausenstr. 40, D-24118 Kiel, FRG mschulz@email.uni-kiel.de

Manfred Mudelsee

Institute of Meteorology, Univ. Leipzig Stephanstr. 3, D-04103 Leipzig, FRG Mudelsee@rz.uni-leipzig.de

Please cite the following reference if you use the program to analyze your data for publications:

Schulz, M. and Mudelsee, M. (in press) REDFIT: Estimating red-noise spectra directly from unevenly spaced paleoclimatic time series. Computers and Geosciences.

DISCLAIMER OF WARRANTY

THIS SOFTWARE PROGRAM AND DOCUMENTATION ARE PROVIDED "AS IS" AND WITHOUT WARRANTIES AS TO PERFORMANCE. THE PROGRAM REDFIT IS PROVIDED WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES WHATSOEVER. BECAUSE OF THE DIVERSITY OF CONDITIONS AND HARDWARE UNDER WHICH THE PROGRAM MAY BE USED, NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS OFFERED. THE USER IS ADVISED TO TEST THE PROGRAM THOROUGHLY BEFORE RELYING ON IT. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS PROGRAM.

1. Installation/Contents of the ZIP Archive

Copy the ZIP-archive to an empty directory and make sure to keep the directory structure when unzipping the archive. With pkunzip this is done using the **-d** option; enter one of the following commands at the DOS prompt:

or

You should end up with the following directory structure:

.\bin Executable files

.\src Fortran 90 source code

.\doc Documentation

.\example Example 1 from Schulz & Mudelsee

2. Running REDFIT

REDFIT requires Win95, NT or above. Change to the .\bin directory and select an executable depending on your CPU:

rf35w4.exe 486 CPU

rf35wp.exe Pentium or MMX CPU

rf35wpp.exe Pentium Pro, II, III or Celeron CPU

All program options and parameters are set in a configuration file that is passed to REDFIT via the command line. An example configuration file (redfit35.cfg) can be found in .\bin. For example, to run the program under Win95 with a Pentium CPU, open a DOS-Box and enter the following command line:

rf35wp redfit35.cfg

2.1 Configuration File Format

The configuration file is in ASCII format and can be edited with any text editor. We recommend that you copy the original **redfit35.cfg** file to a working file in order to have a backup. The configuration file contains a Fortran 90 namelist, e.g.:

```
&cfg
    fnin = 'c:/data/foo.dat',
    fnout = 'c:/data/foo.red',
    nsim = 1000,
    mctest = T,
    ofac = 4.0,
    hifac = 1.0,
        n50 = 3,
    rhopre = -99.0,
    iwin = 2
```

(If you are unfamiliar with namelists, please note the following:

- a string &cfg in the first line and a single slash in the last line
- each data line, except the last, ends with a comma
- filenames must be enclosed in '...' or "..."
- directories are marked by a normal slash and NOT by the usual DOS backslash
- namelist entries can be in lower or upper case
- comment lines are marked by a leading "!")

The parameters in the namelist have the following meaning:

```
fnin
           Input filename with time series data
fnout
           Results are written to this file (ASCII format)
nsim
           Number of Monte-Carlo simulations (1000–2000 should be o.k. in most cases)
           Toggle calculation of false-alarm levels based on Monte-Carlo simulation,
mctest
           if set to T: perform Monte-Carlo test,
           if set to F: skip Monte-Carlo test (default).
           Oversampling factor for Lomb-Scargle Fourier transform (typical values: 2.0–4.0)
ofac
           Max. frequency to analyze is set to hifac * <f<sub>Nvq</sub>> (default = 1.0)
hifac
           Number of WOSA segments (with 50 % overlap)
n50
rhopre
           Prescibed value for \rho; unused if < 0 (default = -99.0)
iwin
           Window-type identifier used to suppress sidelobes in spectral analysis:
```

```
(0: Rectangular
```

- 1: Welch
- 2: Hanning
- 3: Triangular
- 4: Blackman-Harris).

Parameters ofac, hifac, n50 and window type are identical to the SPECTRUM program (see Schulz and Stattegger, 1997 for further details). Except mctest, hifac and rhopre all parameters must be specified.

2.2 Input Data Format

Time series data are read from space- or tab-delimited ASCII files of the following format:

where t(1) < t(2) < ... < t(N) are GEOLOGICAL AGES and not physical times! The maximum number of data points N is only limited by the available amount of memory. The files must not contain more than two data columns. Make sure that the file contains NO BLANK LINES at the end of the file and within the data section. Comment lines are indicated by a leading # and are only allowed at the beginning of the file. The number of comment lines is unlimited.

3. Output

- Estimated parameters and spectra (including false-alarm levels) are written to **FNOUT**.
- Error and warning messages are written to **REDFIT.LOG**.

The output file is in ASCII format and can be processed by the GNUPLOT graphic package or can be imported into most spreadsheets. The contents of the file is subdivided into several sections and should be largely self explanatory:

Input: Lists the main settings from the configuration file.

Initial values:

idum Seed value for random-number generator (generated internally).

Data variance Estimated variance of the data based on the area under the spectrum.

Avg. dt Average sampling interval of the input data (Δt) .

Results:

Avg. tau Estimated values of τ . (Mudelsee, in press. Note that τ is estimated separately for each WOSA segment and subsequently averaged.)

Avg. autocorr. coeff., rho $\rho = \exp(-\Delta t/\tau)$

Degrees of freedom Used for calculating χ^2 percentiles to scale red-noise estimate (see below) to false-alarm levels.

6-dB Bandwidth Resolution bandwidth (in frequency units).

Critical false-alarm level (Thomson, 1990)

==> corresponding scaling factor for red noise

False alarm level = $(1-1/n) \times 100$ %, where n is the number of data points in each WOSA segment. Multiply the red-noise estimate (see below) with the scaling factor to plot the false-alarm level.

Equality of theoretical and data spectrum: Runs test 5-% acceptance region: rcritlo rcrithi

r_test

Check appropriateness of the AR1 model to describe $x(t_i)$ by testing the equality of $G_{rr}(f_j)$ and $\hat{G}_{xx}^{\ \prime}(f_j)$ using a nonparametric runs test. If r_{test} falls outside the interval [rcritlo, rcrithi] the AR1 model is not appropriate to describe the data. In such cases: (i) Check for the presence of harmonic components (can be subtracted using SPECTRUM; Schulz and Stattegger, 1997). (ii) If the misfit occurs at the high frequency end of the estimated spectrum (visual inspection!) reduce hifac

to exclude this frequency range from the calculation. (iii) Prescribe ρ based on your intuition (**rhopre**). Note that the test is only performed with the setting **n50 = 1**, iwin = 0 and hifac = 1

Elapsed time [s]: To check if your neighbors PC is faster than yours.

<u>Data Columns</u>: Meaning of data columns should be largely self explanatory.

- Frequency units = 1/age units
- MC (= Monte-Carlo) false-alarm levels are only calculated if mctest = T
- Spectral amplitudes are scaled such that the area under the spectrum is an estimator for the data variance (provided that hifac= 1.0).
- Usually one plots col. 3, 4 and some out of 7–13 vs. col. 1.

4. Notes and Troubleshooting

- A linear trend is subtracted from each WOSA segment prior to taking the Fourier transform.
- If your computer runs out of memory, try the following

```
- increase n50
- set mctest = F
- reduce nsim (e.g. 500)
- set ofac = 1.0
```

5. Recompiling REDFIT

A Fortran 90 compiler is required to compile REDFIT. The program was successfully compiled with Lahey's LF90 (V. 4.0e) and LF95 (V. 5.6e). The only nonstandard Fortran statements are related to the command line retrieval in the module mutil.f90 and a carriagecontrol = "FORTRAN" specifier in some open statements. The program makes extensive use of the following subroutines from Press et al. (1992, 1996; these routines are not included due to copyright limitations):

```
avevar.f90 erfcc.f90 gammln.f90
```

```
gammp.f90
gasdev.f (we prefer the F77 function instead of the F90 subroutine)
gcf.f90
gser.f90
ran.f90
sort.f90
```

Make sure to modify the include statements at the end of **redfit35.f90** according to your local setting. In addition to these routines, the following modules from Press et al. (1996) are required: **nr.f90**, **nrtype.f90** and **nrutil.f90**.

References

- Mudelsee, M., in press. TAUEST: a computer program for estimating persistence in unevenly spaced weather/climate time series. Computers & Geosciences.
- Press, W. H., Teukolsky, S. A., Vetterling, W. T. and Flannery, B. P., 1992. Numerical Recipes in FORTRAN, 2nd ed. Cambridge University Press, Cambridge. 963 pp.
- Press, W. H., Teukolsky, S. A., Vetterling, W. T. and Flannery, B. P., 1996. Numerical Recipes in Fortran 90. Cambridge University Press, Cambridge. 571 pp.
- Schulz, M. and Stattegger, K., 1997. SPECTRUM: Spectral analysis of unevenly spaced paleoclimatic time series. Computers & Geosciences, **23**, 929-945.
- Thomson, D.J., 1990. Time series analysis of Holocene climate data. Philosophical Transactions of the Royal Society of London, Series A 330, 601-616.